

2998 Photodiode Array Detector

The 2998 Photodiode Array (PDA) Detector offers advanced optical detection, providing unprecedented trace impurity detection and quantification in conjunction with spectral analysis capabilities. It is the ideal detector for any lab application from compound identification to method development. For routine analyses, the 2998 PDA Detector is reliable, easy-to-use, and has enhanced software control to provide flexibility for simultaneous 2D and 3D operation.



OPERATING SPECIFICATIONS¹

Wavelength range	190 to 800 nm
Wavelength accuracy	±1 nm (via patented ² Erbium filter)
Wavelength repeatability	±0.1 nm
Bandwidth	1.2 nm
Photodiodes	512
Digital resolution	1.2 nm/pixel
Linearity range	≤5% at 2.0 AU, propylparaben, 257 nm
Baseline noise ³	≤10 x 10 ⁻⁶ AU, 254 nm 2 points/s, 1.0 s, 30 s segments, dry analytical flow cell
Drift	≤1.0 x 10 ⁻³ AU/hour/°C, 254 nm dry analytical flow cell
Sampling rate	Up to 80 points/s

OPTICAL COMPONENT SPECIFICATIONS

Light source	Deuterium arc lamp Warranty: 2000 hours or one year (whichever comes first)
Flow cell design	Patented TaperSlit™ ⁴
Path length	10 mm (analytical flow cell)
Flow cell volume	8.4 µL (analytical flow cell)
Pressure limit	1000 psi (analytical flow cell)
Wetted materials	316 stainless steel, fused silica, FEP, Tefzel

ELECTRICAL SPECIFICATIONS

Power requirements	100 to 240 VAC
Line frequency	50 to 60 Hz
Power consumption	195 VA (nominal)
Inputs	Four event inputs
Outputs	Four outputs (2 analog, 2 event)

PHYSICAL/ENVIRONMENTAL SPECIFICATIONS

Dimensions	Width: 34.3 cm (13.5 inches) Height: 20.8 cm (8.2 inches) Depth: 61.0 cm (24.0 inches)
Weight	14.5 kg (32 pounds)
Operating temperature range	4 to 40 °C (39.2 to 104 °F)
Operating humidity range	20% to 80%, non-condensing
Audible noise	<58 dBA

ORDERING INFORMATION

PART NUMBER

2998 Photodiode Array Detector

176299801

Optional flow cells:

Analytical*	8.4 µL volume, 10 mm pathlength	205001023
-------------	---------------------------------	-----------

Microbore	2.7 µL volume, 8 mm pathlength	205001024
-----------	--------------------------------	-----------

Semi-preparative	16.3 µL volume, 3 mm pathlength	205001025
------------------	---------------------------------	-----------

Autopurification	12.3 µL volume, 0.5 mm pathlength, dual flow path	205001026
------------------	--	-----------

1. All performance specifications are measured following a warm-up period of one hour with ambient $\Delta T \leq \pm 2.0$ °C
2. U.S. Patent Numbers: 6,423,249 and 6,783,705
3. ASTM E16657-98
4. U.S. Patent Numbers: 5,883,721

*Included with detector.

Waters

THE SCIENCE OF WHAT'S POSSIBLE.™



Waters is a registered trademark of Waters Corporation. Empower, MassLynx, TaperSlit, and The Science of What's Possible are trademarks of Waters Corporation. All other trademarks are the property of their respective owners.

©2012 Waters Corporation. Produced in the U.S.A.
December 2012 720004519EN TC-PDF

Waters Corporation
34 Maple Street
Milford, MA 01757 U.S.A.
T: 1 508 478 2000
F: 1 508 872 1990
www.waters.com